



EN:61010-1

EN:61326-1



■ UT151A



■ UT151B

### SPECIFICATIONS



Specifications	Range	Best Accuracy	
		UT151A	UT151B
Model		UT151A	UT151B
DC Voltage (V)	200mV/ 2V/ 20V/ 200V/ 1000V	±(0.5%+1)	±(0.5%+1)
AC Voltage (V)	2V/ 20V/ 200V/ 750V	± (0.8%+3)	± (0.8%+3)
DC Current (A)	200µA/ 2mA/ 200mA/ 20A	± (0.8%+1)	± (0.8%+1)
AC Current (A)	200µA/ 2mA/ 200mA/ 20A	± (1%+3)	± (1%+3)
Resistance (Ω)	200Ω/ 2KΩ/ 20KΩ/ 200KΩ/ 2MΩ/ 20MΩ/ 200MΩ	±(1%+2)	±(1%+2)
Capacitance (F)	20µF/ 200µF	±(5%+4) >100µF Reference Only	
	2nF/ 20nF/200nF/2µF/ 100µF		±(4%+3)
<b>Features</b>			
Display Count		1999	1999
Manual Range		✓	✓
Battery Test	12V/ 9V/ 1.5V	±(2.5%+2)	
Diode		✓	✓
Auto Power Off		✓	✓
Continuity Buzzer		✓	✓
Low Battery Indication		✓	✓
Data Hold		✓	✓
Input Impedance for DCV	≥10MΩ	✓	✓

### GENERAL CHARACTERISTICS

Power	9V Battery (6F22)
LCD Size	63mm × 29mm
Product Color	Red and Grey
Product Net Weight	300g
Product Size	186mm × 91mm × 39mm
Standard Accessories	Battery, Test Lead
Standard Individual Packing	Gift Box, English Manual
Standard Quantity Per Carton	40 PCs
Standard Carton Measurement	645mm × 450mm × 340mm (0.099 CBM Per Standard Carton)
Standard Carton Gross Weight	22.8 Kg