



EN:61010-1

EN:61326-1



■ UT151C



■ UT151D



■ UT151E

SPECIFICATIONS

Specifications	Range	Best Accuracy		
		UT151C	UT151D	UT151E
Model		UT151C	UT151D	UT151E
DC Voltage (V)	200mV/ 2V/ 20V/ 200V/ 1000V	±(0.5%+1)	±(0.5%+1)	±(0.5%+1)
AC Voltage (V)	2V/ 20V/ 200V/ 750V	±(0.8%+3)	±(0.8%+3)	±(0.8%+3)
DC Current (A)	2mA/ 20mA/ 200mA/ 20A	±(0.8%+1)	±(0.8%+1)	±(0.8%+1)
AC Current (A)	20mA/ 200mA/ 20A	±(1%+3)	±(1%+3)	±(1%+3)
Resistance (Ω)	200Ω/ 2KΩ/ 20KΩ/ 200KΩ/ 2MΩ/ 20MΩ	±(1%+2)	±(1%+2)	±(1%+2)
	200Ω/ 2KΩ/ 20KΩ/ 200KΩ/ 20MΩ/ 200MΩ			±(1%+2)
Capacitance (F)	2nF/ 20nF/ 200nF/ 2μF/ 100μF	±(4%+3)	±(4%+3)	±(4%+3)
	20nF/ 200nF/ 2μF/ 100μF		±(4%+3)	±(4%+3)
Frequency (Hz)	2KHz		±(2.0%+5)	±(1.5%+5)
	20KHz		±(1.5%+5)	±(1.5%+5)
Temperature (°C)	-40 °C ~ 1000°C	±(1%+3)		±(1%+3)
Temperature (°F)	-40°F ~ 1832°F	±(1%+4)		
Features				
Display Count		1999	1999	1999
Manual Range		✓	✓	✓
Diode		✓	✓	✓
Auto Power Off		✓	✓	✓
Continuity Buzzer		✓	✓	✓
Low Battery Indication		✓	✓	✓
Data Hold		✓	✓	✓
Input Impedance for DCV	≥10MΩ	✓	✓	✓

GENERAL CHARACTERISTICS

Power	9V Battery (6F22)
LCD Size	63mm × 29mm
Product Color	Red and Grey
Product Net Weight	300g
Product Size	186mm × 91mm × 39mm
Standard Accessories	UT151C/UT151E- Battery, Test Lead, Point Contact Temperature Probe UT151D- Battery, Test Lead
Standard Individual Packing	Gift Box, English Manual
Standard Quantity Per Carton	40 PCs
Standard Carton Measurement	645mm × 450mm × 340mm (0.099 CBM Per Standard Carton)
Standard Carton Gross Weight	22.8 Kg