

PLC-310 Programmable Logic Controller (MITSUBISHI PLC) Trainer



Features

- 1. Input-simulation switches with level and pulse Input are functioning to meet the need of different input signal.
- Output Relay's installation helps to increase load current. Easy-to-use,windows-based development software
- Assorted peripheral devices and other devices that can support external extensions, it particularly suits for laboratory experiment and project implementation.
- Various simulations I/O devices to facilitate study and observe the results.
- 5. Using 4mm safety sockets on Input/Output terminals to ensure users' safety.
- 6. The suitcase-design makes it easy to carry, move and store.

Specifications

- 1. AC Power Supply : 100V ~ 240V AC, 50Hz/60Hz
- 2. PLC Main Unit : MITSUBISHI FX_{3UC}-32MT
- 3. Digital Input : 16
- 4. Digital Output : 16
- 5. Support High-speed Counters : 8 (total)
- 6. Support Timers : 256 total timers, 4 timers (1ms), 46 timers (10ms), 206 timers (100ms)
- 7. Communication Ports : RS-422
- 8. 4-digit 7-segment Display
- 9. 4-digit Thumbwheel Switch
- 10. Module Expansion Port and DIO Extension Port
- 11. Traffic Light Control Module
- 12. Tank-filling Device Module
- 13. Step Motor
- 14. Encoder
- 15. 24V DC Motor
- 16. Proximity Sensor
- 17. Micro Switch
- 18. Buzzer
- 19. 4x4 Keypad
- 20. 24V DC Expansion Power
- 21. Windows-based programming software (GX-developer) allows the user to modify the program while running it

List of Experiments

- 1. Gx-developer Operations
- (1) Editing Ladder Program
- (2) Testing Ladder Program
- (3) Monitoring Status

Since PLC (Programmable Logic Controller) was firstly introduced in 1970, it has been widely applied to various industrial uses such as machine and process controls. Designed with the latest microprocessor and electronic circuitry, today's compact-size PLCs feature high level of reliability, performance, speed and networking. The use of PLCs in automated production lines improves system reliability, product quality, information sharing, efficiency and flexibility and thus reduces costs. PLC-310 is a selfcontained trainer which consists of a MITSUBISHI PLC main unit, I/O devices for simulation and I/O devices that are commonly used. It provides students with a thorough understanding of the theories and applications of programmable logic controllers. This trainer enables students to learn step by step the fundamentals of PLC and more advanced controls used in industry.

- 2. Basic Control Circuits
 - (1) Self-holding Circuit
 - (2) Flashing Control
 - (3) Inching Control
 - (4) Single-button Control
- 3. Light Control
 - (1) Simple Light Control
 - (2) Complex Light Control
- 4. Traffic Light Control
 (1) Traffic Light Controller (conventional)
 (2) Traffic Light Controller (step)
- 5. Digital Clock Control
 - (1) 7-Segment Display Control(2) Time Clock
- 6. Step Motor Control
 - (1) Speed and Direction Control
 - (2) Encoder Operation
 - (3) Step Motor and Encoder
 - (4) Step Motor's Step Display
- 7. Tank Filling Device Control
 - (1) Tank Filling Control
 - (2) Tank Filling Control with Thumbwheel
- 8. Keypad Control
 - (1) Keypad Operation
 - (2) Digital Lock Control
- 9. DC Motor Control
 - (1) PWM Speed Controller
 - (2) Proximity and Micro Switches
 - (3) Automatic Speed Control

•System Requirements

- 1. PC with Pentium II or Better CPU
- 2. Windows 7 / 10
- 3. User's Manual (optional)
- 4. GX-developer Software CD with E-manual (It is necessary to prepare locally)

Accessories

- 1. Power Cord
- 2. Experiment Manual
- 3. Connecting Leads Set
- 4. USB-422 Cable