

UT61E**Modern Digital Multimeters****SPECIFICATIONS**

Basic Functions	Range	Best Accuracy
DC Voltage	220mV/2.2V/22V/220V/1000V	±(0.1%+2)
AC Voltage	220mV/2.2V/22V/220V/750V	±(0.8%+10)
AC Current	220μA/2200μA/22mA/220mA/2.2A/10A	±(0.8%+10)
DC Current	220μA/2200μA/22mA/220mA/2.2A/10A	±(0.5%+10)
Resistance	220Ω/2.2KΩ/22kΩ/220kΩ/2.2MΩ/22MΩ/220MΩ	±(0.5%+10)
Capacitance	22nF/220nF/2.2μF/22μF/220μF/2.2mF/22mF/220mF	±(3.0%+5)
Frequency	10Hz-220MHz	±(0.01%+5)
Frequency Response		45Hz~10kHz
Duty Cycle	0.1%~99.9%	✓
Special Functions		
Auto/Manual Ranging		✓
Diode		✓
RMS		✓
Continuity Buzzer		✓
Data Hold		✓
Peak Value		✓
Display Backlight		✓
REL		✓
Sleep Mode	Around 15 Minutes	✓
Analogue Bar Graph		46
RS232		✓
Input Protection		✓
Input Impedance for DC Voltage Measurement	Around 10MΩ	✓
Low Battery Display	≤7.5V	✓
Max Display		22000

GENERAL CHARACTERISTICS

Power	9V Battery (6F22)
LCD Size	65 x 43mm
Product Colour	Red and Grey
Product Net Weight	370g
Product Size	180 x 87 x 47mm
Standard Accessories	Battery, Test Lead, English Manual, Multi-Purpose Socket, RS232 Interface Cable, Software
Optional Accessories*	USB Interface Cable
Standard Individual Packing	Gift Box
Standard Quantity Per Carton	20pcs
Standard Carton Measurement	465 x 335 x 345mm (0.054 CBM Per Standard Carton)