

UNI-T® UT132 SERIES

Palm Size Digital Multimeters

UT132A ■ UT132B



EN:61010-1
EN:61326-1



■ UT132A

SPECIFICATIONS



Specifications	Range	Best Accuracy	
		UT132A	UT132B
Model		UT132A	UT132B
DC Voltage (V)	200mV/ 2000mV/ 20V/ 200V/ 250V	±(0.5%+2)	±(0.5%+2)
AC Voltage (V)	200V/ 250V	±(1.2%+3)	±(1.2%+3)
DC Current (A)	2000µA/ 20mA/ 200mA/ 10A	± (1%+2)	± (1%+2)
Resistance (Ω)	200Ω/ 2000Ω/ 20KΩ/ 200KΩ/ 2000KΩ/ 20MΩ	±(0.8%+5)	±(0.8%+5)
Features			
Display Count		1999	1999
Manual Range		✓	✓
Battery Test	1.5V/ 9V		± (1%+2)
Square Wave Output		✓	
Diode		✓	✓
Transistor		✓	✓
Continuity Buzzer			✓
Low Battery Indication		✓	✓
Data Hold		✓	✓
Input Impedance for DCV	Around 10MΩ	✓	✓



■ UT132B

GENERAL CHARACTERISTICS

Power	9V Battery (6F22)
LCD Size	49mm × 18mm
Product Color	Red and Grey
Product Net Weight	200g
Product Size	72mm × 137mm × 35mm
Standard Accessories	Battery, Test Lead, Multi-Purpose Socket
Standard Individual Packing	Gift Box, English Manual
Standard Quantity Per Carton	40 PCs
Standard Carton Measurement	540mm × 365mm × 290mm (0.057CBM Per Standard Carton)
Standard Carton Gross Weight	13.8 Kg