



IEC:1010-1  
IEC:1010-2-032  
IEC:61326

# NEW



### SPECIFICATIONS

Specifications	Range	Best Accuracy	
Model		UT276A	UT278A
Earth Ground Resistance (Ω)	0.01Ω~0.099Ω	±(1%+0.01)	±(1%+0.01)
	0.1Ω~0.99Ω	±(1%+0.01)	±(1%+0.01)
	1.0Ω~49.9Ω	±(1%+0.1)	±(1%+0.1)
	50Ω~99.5Ω	±(2%+0.5)	±(2%+0.5)
	100Ω~199Ω	±(3%+1)	±(3%+1)
	200Ω~395Ω	±(6%+5)	±(6%+5)
	400Ω~590Ω	±(10%+10)	±(10%+10)
	600Ω~800Ω	±(20%+20)	±(20%+20)
Leakage Current(A)	800Ω~1200Ω	±(25%+30)	±(25%+30)
	0mA~9mA		±(2.5%+1)
	10mA~99mA		±(2.5%+5)
	100mA~299mA		±(2.5%+10)
	0.30A~2.99A		±(2.5%+0.1)
	3.0A~9.9A		±(2.5%+0.3)
	10.0A~20.0A		±(2.5%+0.5)
3A~30A		±(2.5%+0.5)	
<b>Features</b>			
Display Count	4 Digits Display LCD	✓	✓
Auto Range		✓	✓
Jaw Capacity		32mm	32mm
Single Measure Time	1 Second	✓	✓
Resistance Measurement Frequency	> 1KHz	✓	✓
Current Measurement Frequency	50Hz/60Hz	✓	✓
Resistance Limit Alarm	1Ω~199Ω	✓	✓
Current Limit Alarm	1mA~499mA		✓
RS-232		✓	
Beeper and Light Alarm		✓	✓
Jamming Signal Recognition		✓	✓
Over-Range Display		✓	✓
Low Battery Indication		✓	✓
Data Logging		99	99



■ UT276A



■ UT278A

### GENERAL CHARACTERISTICS

Power	1.5V Alkaline Batteries (LR6) × 4
LCD Size	47mm × 28.5mm
Product Color	Red and Grey
Product Net Weight	1160g
Product Size	285mm × 85mm × 56mm
Standard Accessories	Batteries, Test Ring, Tool Box
Standard Individual Packing	Gift Box, English Manual
Standard Quantity Per Carton	6 PCs
Standard Carton Measurement	610mm × 375mm × 320mm(0.073 CBM Per Standard Carton)
Standard Carton Gross Weight	25Kg
Optional Accessories	USB Interface Cable, PC Software CD